



Vessel Faucet Installation Instructions

Waterfall faucets and vessel sinks are a great combination commonly installed in today's bathroom. Water comes out of the faucet and cascades into the sink, creating a waterfall appearance.

NOTE: Each Novatto faucet should be installed by a professional.
Abide and follow all building codes.

- Turn the handles on both the hot and cold water supply pipes off so water will not be running through the pipes. These pipes will be located either in the wall or under the sink by the cabinet.

- Wrap white plumbers tape around the two threaded ends of the supplied water supply hoses. (Be sure the tape is correctly placed onto the threads). Place these hoses into the water supply holes on the bottom of the faucet. Tighten the hoses to secure them in place.

- Fasten the two bolts into the two threaded holes in the faucet. Place the round rubber gasket over the faucet hole and slowly lower the faucet onto the gasket.

- Holding the faucet in place slide the half moon rubber gasket and washer up the bolts. Take the two fastening nuts and tighten accordingly. (Depending on the counter thickness you may be able to place the gasket and moon washer on before placing it).

- Attach the flexible water lines on the left to the hot water supply line located behind your sink. The flexible water line on the right should be attached to the cold water supply line located behind your sink. Tighten these connections accordingly.

- Slowly turn the handles on the hot and cold water supply lines to the open position. Turn the waterfall faucet on and allow it to run for a few minutes to get rid of any air pockets in the pipes.

- Enjoy our dedication.