Reliance[®] **R60420DI**

59.5" x 41.5" x 21.75"

Installation: Drop-in

cannot be undermounted

GENERAL SPECIFICATIONS:

Material Acrylic **Plumbed Weight** 99 lbs / 45 kg **Soaker Weight** 75 lbs / 34 kg

42 gal to above jet level Average Fill **Maximum Fill** 88 gal to overflow


NOTE: Filling this tub to the maximum may require an above average size or dedicated water heater.

ELECTRICAL SPECIFICATIONS:

110 Volt **Required Electrical Service Air Bath or Whirlpool** 1-15 amp GFCI Whirlpool with Inline Heater 1-15 amp GFCI Soaker with Inline Heater 1-15 amp GFCI Air Bath with Inline Heater 2-15 amp GFCI CSA Certified C/US; ANSI Z124.1 for plastic tubs and ANSI 112.19.7 for whirlpool

41 1/2" 203/4

Shown with Whirlpool Package.



ANSI Z124.1-1995 CSA Certified C/US

Compliance Label

Model MTXXXX Made in USA Complies with

PACKAGES AND OPTIONS

Hydrotherapy Package	Package Contents	Part #
Soaker	soaking bath - no jets; textured bottom	R6042ODIS
Whirlpool	6 point-massage jets, 1-bhp pump	R6042ODIW
Air Bath	12 air jets, heated air blower, pre-leveled foam base (increases overall height 2-3")	R6042ODIA

Features integral armrests.

OPTIONS

Standard Colors - White **Color Upgrade** - Biscuit (RCOLOR)

Quick Ship - reduces lead time - call for availability Soaker or Whirlpool - ships within 48 hrours (RQSHIP)

Air Bath - ships within 72 hours (RQSHIPA)

Inline Heater - Whirlpool (RHTI)

Inline Heater with Pump - Soaker or Air Bath (RHTISOAK)

Lift & Turn Drain Kit -

Chrome (RWOC); Brushed Nickel (RWOBN), White (RWOW)

Tile Flange -

Field-Installed (RTFKNI)

Kit includes ABS material and adhesive for 3 sides of coverage

IMPORTANT INFORMATION

- · Before ordering or installing, please consider future access to
- Add bedding compound to fully level and support bottom of tub.
- Tubs equipped with an air bath or a pre-leveled foam base are designed to rest on the floor without bedding compound, provided the floor is level.
- Overall tub height is increased by approx. 2-3" when tub is equipped with any air bath package or when pre-leveled foam base or framing system is ordered.
- Please measure tub on-site before building tub decking.
- Jet, pump & blower locations are predetermined and cannot be changed.
- Suction and control locations may vary.
- Specifications and configurations are subject to change without notice.
- Measurements are $\pm 1/2$ " and are subject to change without notice.
- Measurements herein supersede all others published prior to publication date shown below.